

ANNEXURE III

Pkg No-1

NIT Value-Rs 3616278.00

Improvement of 1)Anaity Satra Bhagwati Path, Ward No 12 2) Bishnu Nagar Path Bye Lane 1 Ward No 14 3)Durlav Borgohain Path Ward No 5 4) Prshanti Path near hotel Sarnaz ward No 14 under 15th Finance Commission United Basic Grant(1st Installment) for the year 2020-21 during the year 2020-21.

Sl. No.	Description of Item	Unit	Quantity	Dept. Rate in figure(Rs)	Quoted Rate in figure(Rs)	Rate in words	Amount(Rs)
1	2	3	4	5	6	7	8
1/3.18	Construction of Subgrade and Earthen Shoulders (Construction of subgrade and earthen shoulders with approved material obtained from borrow pits with all lifts & leads, transporting to site, spreading, grading to required slope and compacted to meet requirement of table (300-2) (a), (Including cost of testing of materials						
	(a) from private land	m3	200.5823	327.70			
2/4.2	Construction of granular sub-base by providing coarse graded material, spreading in uniform layers with motor grader on prepared surface, mixing by mix in place method with rotavator at OMC, and compacting with vibratory roller to achieve the desired density, complete as per cl.401						
	(ii) For Grading-II Materials	m3	227.4277	2,695.67			
3/4.9/A. (iii)	Providing, laying, spreading and compacting stone aggregates of specific sizes to water bound macadam specification including spreading in uniform thickness, hand packing, rolling with Smooth wheeled steel roller 80-100 KN in stages to proper grade and camber, applying and brooming requisite type of screening/binding material to fillup the interstices of coarse aggregate, watering and compacting to the required density Grading 3 as per Technical Specification Clause 405.						
	By Manual Means	m3	136.4875	4,243.11			
	For Grading-III Materials						
	Using Screening Type -B (11.2 mm Agg.)						

4/17.40 (a)	Providing and laying Interlocking Concrete Block Pavement (ICBP) conforming to IS:15658-2006 including all lead and lift complete as per technical specification and as directed.						
	80mm thick interlocking precast blocks having compressive strength of 40N/sq.mm.	sqm	1,822.50	910.21			
5/ 17.40 (c)	Providing and laying Interlocking Concrete Block Pavement (M-40) having thickness 80mm as per technical specification Clause 1504 complete including carriage.	Cum	54.851	10,751.04			
6/8.4	Providing and fixing of retro-reflectorised cautionary madatory and informatory sign as per IRC:67 made of encapsulated lens type reflective setting vide Cl.1701.2.3 fixed over aluminum sheeting, 1.5 mm thick supported on a mild steel Engle iron post 75mm X 75mm X 6mm firmly fixed to the ground by means of properly designed foundation with M15 grade cement concrete 450mm X 450mm X 600mm, 600mm below ground level as per drawings and Technical Specification Clause 801.						
	ii) 60 cm equilateral tringle	No.	4	4,578.76			
	iii) 60 cm Circular	No.	4	6,098.61			

7/8.6	<p>Direction and place identification sign more than 0.9sqm size board.</p> <p>Providing and erecting direction and place identification retro-Reflectrorised sign as per IRC:67 made of encapsulated lens type reflective sheeting vide clause 801.3 fixed over aluminium sheeting, 2mm thick with area exceeding 0.9sqm fixed on an angle iron of 25x25x4mm supported on a mild steel angle iron post 75mm x 75mm x 6mm, 2 nos. firmly fixed to the ground by means of properly design foundation with M-15 grade Cement concrete 45cm x 45cm x 60cm, 60cm below ground level as per approved drawing and sign. . (All the Steel work must be Tata/Sail/or any other approved brand) Size:- 1.20m x 0.90m = 1.08 sqm.</p>	sqm	4.32	15,526.20			
	Total=						